

ISGUS Terminal IT 8260



Multifunctional touch screen terminal for:

- » Time & Attendance
- » Web Workflow
- » Cost Centre Recording
- » Production Data Capture

Ideally suited for rugged industrial environments



IT 8260 for Time & Attendance and Workflow

- » Touch screen with large coloured symbols and function buttons for convenient handling
- » Supports time booking actions (such as IN and OUT) as well as cost centre change bookings
- » Time bookings via IN/OUT keys or automatic bookings
- » Easy generation of workflow requests via touch screen for absences, such as holidays, business trips, vocational training, etc. or insertion of missing bookings or booking updates
- » Retrieval of up-to-the-minute information on any time account, such as working time balance, overtime, remaining holiday entitlement, etc.
- » Booking of absences for specific reasons, e. g. business trip, business travel, doctor's appointment, etc.
- » Storage of up to 50,000 bookings

- » Multi-client capability
- » Seamless integration into existing IT environments via DHCP and DNS support



IT 8260 for Production Data Capture

- » Easy and quick selection and entry of orders and PDC bookings, like order start/change/end, good yield and rejects quantity, etc. directly on the touch screen
- » USB port allowing for secure PDC data capture via connectable barcode reader or QR scanner
- » Durable and robust housing with seamless matt glass panel for easy cleaning
- » Scratch-resistant glass front (3 mm) for optimum touch screen protection

Technical Information Terminal

IT 8260



Badge reading technologies

- » ISGUS Prox
- » Hitag 1
- » LEGIC
- » LEGIC advant
- » Mifare
- » Mifare DESFire
- » Em4102
- » Others upon request

Touch screen

- » 15" TFT colour graphics display with capacitive touch function
- » Resolution: 1024 x 768
- » Touch surface made of glass: 3 mm, two point projected capacitive technology

Power supply

- » Integrated power supply unit with supply voltage of 230V

Typical power consumption

- » 16.1 W

Protection type

- » IP 65 (front side)

Protection class

- » I / En 62368-1

Rel. humidity

- » Max. 85 %

Ambient temperature

- » -5°C to +40°C

Network connection

- » Ethernet 10/100/1000 MBit/s
- » RJ-45

Weight

- » Approx. 4.5 kg

Dimensions

- » Height: 334 mm
- » Width: 360 mm
- » Depth: 90 mm

